



SERIES 08R – GUIDE SPECIFICATION

BELTED RING FANS, REVERSE FLOW

The Belted Ring Fans, Reverse Flow shall be manufactured by Hartzell Air Movement Series 08R; standard sizes are 24" through 72". The fan shall be packaged, completely assembled and ready to install.

The belted ring propeller shall be an airfoil design, cast of 319 aluminum in compliance with Federal Specification QQ-A-601E and ASTM B26. Propellers shall be retained on the fan shaft utilizing a split taper bushing or a clamp block arrangement. The fan bearings shall be heavy duty, self-aligning ball type and relubricable selected for continuous service. The belts shall be oil, heat and static resistant, sized for continuous duty. Fixed pitch drives shall be standard.

Solid rolled rod motor mounts shall provide support for the motor. Motors shall be totally enclosed air over type. All fractional motors shall be permanently lubricated, non-regreasable. Integral horsepower motors shall be supplied with regreasable bearings. Fans shall be designed for mounting in any position from horizontal to vertical.

The propeller shall be mounted in a high efficiency air seal fan orifice with the smaller diameter of the ring overlapping the propeller tips. Standard surface coating system shall be phosphatized surface preparation with an industrial grade air dry enamel paint.

The fan assembly shall be dynamically balanced at the Hartzell factory prior to shipping. Fans shall be balanced in accordance with AMCA Standard 204, fan application category BV-3 (comparable to Grade G6.3). Fans shall be manufactured in accordance with Hartzell's standard quality assurance procedures. Fan performance shall be based on tests conducted in Hartzell's AMCA accredited test laboratory and conducted in accordance with the latest revision of AMCA Standard 210 for air performance and AMCA Standard 300 for sound performance. Fans shall be licensed to bear the AMCA Certified Air Performance Rating Seal.

ACCESSORIES:

- Special Construction - Available in stainless steel and aluminum.
- Protective Coatings - Available coatings include epoxy and inorganic zinc. Other specialty coatings may be available - **Consult Factory**.
- Motors - Special motors can be furnished upon request.
- Inlet/Outlet Guards - Concentric ring, expanded metal and woven wire guards.
- Shutter Mounting Boot - Available for mounting fans and automatic, manual, or motor operated shutters.
- Flat Panels - For mounting ring fans to various sizes of wall openings or mounting boots.
- Wall Hoods - Heavy duty steel or aluminum for protecting the fan and building opening from the weather.
- Filter Boxes - For use with ring fans to filter supply air.